



PRODUCTS

COLD REDUCED

BS EN 10130: 2006
DC01
DC04

Thickness Range 0.5mm – 3.0mm

Widths Available 1000mm 1250mm 1500mm

Lengths up to 4470mm

GALVANISED

BS EN 10346:2009
DX51D

Surface Finishes Available

NA – Normal Spangle
MA – Minimised Spangle
MB – Minimised Spangle Improved Surface
MC – Minimised Spangle Best Quality Surface

Thickness Range 0.5mm – 3.0mm

Widths Available 1000mm 1250mm 1500mm

Lengths up to 4470mm

ELECTRO ZINC

BS EN 10152:2009 2.5Micron Coating

Thickness Range 0.5mm – 3.0mm

Widths Available 1000mm 1250mm 1500mm

Lengths up to 4470mm

FLOOR PLATE

BS EN 10025:2004
S275JR (43A)

Thickness Range 3.0mm – 12.0mm

Widths Available 1000mm 1250mm 1500mm

Lengths up to 18000mm

HOT ROLLED

BS EN 10111:2008
DD11 (HR4)
DD12 (HR2)
DD13 (HR1)

Thickness Range 1.5mm – 6.0mm

Widths Available 1000mm 1250mm 1500mm 1830mm
2000mm

BS EN 10025:2004
S275 JR (43A)

Thickness Range 3.0mm – 12.5mm

Widths Available 1000mm 1250mm 1500mm 1830mm
2000mm

Lengths up to 18000mm

S355 JR (50B)

Thickness Range 3.0mm – 12.5mm

Widths Available 1000mm 1250mm 1500mm 1830mm
2000mm

Lengths up to 18000mm

HOT ROLLED PICKLED & OILED

BS EN 10111:2008
DD11 (HR4)

BS EN 10025:2004
S275 JR (43A)

Thickness Range 1.6 – 12.5mm

Widths Available 1000mm 1250mm 1500mm

Lengths up to 18000mm

SHEET AND BLANKS

SLIT COIL